

CHAPTER ELEVEN

ALIGN®

CHAPTER OUTLINE

Introduction

Jeffrey Court's design objective with Chapter 11 Align® was to bring clean lines and shapes to the collection. This is synonymous with the word align, defined as bringing components into desirable coordination, thus capturing the essence of Chapter 11 perfectly.

Key Features

1. Colors

- Offered in Chapter 11 are three beautiful natural stones: Two Portuguese limestones named Pale and Shadow, as well as one grey Turkish marble named Suede. All Chapter 11 stone finishes are honed to a smooth satin surface which complement the simple design elements.

2. Field Tiles

- The four field tiles sizes are offered in linear 3" x 10" and 6" x 18" bar tiles, a classic 8" hexagon and, a 6" x 7 15/16" diamond. As with all of our collections, Chapter 11 Align has all of the necessary decorative tiles, mouldings, and domes to make any installation a resounding success.

3. Mosaics

- Align features nine distinctive mosaic patterns assembled in a clean, minimalist style. Three patterns (Convex, Herringbone Styx, and Trax) come in monochromatic colors while the remaining six patterns (Harmony, Hex Mixed Medley, Jax, Merge, Stax, and Woven) are offered in beautiful, multicolored blends.

4. Decorative Elements

- One of the most stunning features of Chapter 11 is its Drawn Stone elements. Boasting a total of four patterns, Drawn Stone utilizes the latest imaging and patented UV curing process to lock images on our diamond and hex Pale limestone, making them true pieces of art.

5. Mouldings

- Three moulding pieces are offered in this collection: a 1 7/8" x 11 7/8" crown, 1 7/8" x 11 7/8" rex crown, and a 3/4" x 11 7/8" dome.

Application

Please reference the Application Chart for Chapter 11 on our website, JeffreyCourt.com, for more details on recommended applications.

Testing

Product specifications are listed on each product specific web page on JeffreyCourt.com. If available, testing results for applicable products: ceramic, glass, and porcelain, can be found on the back of the respective chapter catalog for easy reference. Due to the ever-changing nature of stone products, Jeffrey Court does not test natural stone products.

Installation Tips

1. Blending and Shade Variation

- To achieve your desired look, Jeffrey Court recommends that you inspect and confirm the tile and layout prior to installation. Installation of tile constitutes acceptance.
- For natural stone collections, it is highly recommended to blend products from multiple cartons to ensure a proper uniform look. All issues pertaining to shade variation should be addressed prior to installation.

2. Rating

- For specific item-by-item shade variation rating, please reference each product specific web page on JeffreyCourt.com.

3. Setting Materials and Grouts

- A high-quality white thinset meeting ANSI 118.4 or 118.11 is recommended for best installation results. Always check with setting material manufacturer to ensure suitability of material in setting tiles. A grey mortar, or mastic or adhesives could stain or alter the color of the product.
- A natural look penetrating sealer is recommended and should be used before and after grouting sealing before grouting will ease the cleaning process and will reduce the possibility of staining from colored grouts. Sealing after grouting will ensure that both the grout and natural stone are protected from daily use. It is recommended that the sealer manufacturer's recommended maintenance regimen be followed as part of an ongoing care during the lifetime of the product.
- As per the Tile Council of North America (TCNA): "For cementitious grout, joints smaller than 1/8" generally should only be grouted with unsanded grout, and joints of 1/8" and larger should only be grouted with sanded grout."
- Grout color is part of the design process and considerations must be made. A grout choice closest to the color and hue of the tile being grouted can be considered the safest choice.
- Please see enclosed Drawn Stones Care & Maintenance Instructions for complete product details, procedures, and precautions.

*Urethane grout was used on the touch boards for this collection. Pre-sealing any matte/frosted tiles prior to grouting with urethane grout is required. Suggested recommendation: Aqua Mix® Grout Release.

4. Cutting

- A professional grade wet saw outfitted with a high-quality diamond blade designed for cutting tiles is recommended. Always cut tiles with the face up.

⚠ WARNING: This product can expose you to chemicals including crystalline silica which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

CAUTION: SILICA DUST HARMFUL IF INHALED. Exposure to silica dust from cutting, grinding, or polishing can cause acute lung injury, silicosis, or cancer. Wear a respirator when cutting, grinding, or polishing. Use wet cutting methods and do not dry cut. Children should not be present during cutting, grinding, or polishing. For more information, see the SDS at www.jeffreycourt.com.

Merchandising

The marketing and merchandising of this collection is supported by montage boards, touch boards, and sample cards which aid in displaying the full product line. All these point of purchase materials are accompanied by the Chapter 11 Align catalog. Showroom installation and loose sample pieces can also be ordered at a discounted price.

Visit the Jeffrey Court website, JeffreyCourt.com, to gain inspiration on the design possibilities offered with Chapter 11 Align.