

CHAPTER 4 - VIA

TECHNICAL DATA

S P E C S

SERIES: Chapter 4 - VIA**COLOR:** Cream, Brown, Clay**ITEM:** Sierra Hexagon Glass Mosaic
Sierra Penny Glass Mosaic**FINISH:** Matte**APPLICATION SUITABILITY**

APPLICATION	SUITABILITY	APPLICATION	SUITABILITY
Wall	Yes - Interior/Exterior	Wet areas	Yes
Floor	Yes - Residential	Pool	Yes

TECHNICAL CHARACTERISTICS	TEST METHOD	AVERAGE VALUES
Water absorption	ISO 10545-3	No
Mohs hardness	UNE-6701	5
Thermal shock resistance	ISO 10545-9	Yes
Frost resistance	ISO 10545-12	Yes
Domestic products	ISO 10545-13:1998	GA
Pool water additives	ISO 10545-13:1998	GA
Low acid and alkalins	ISO 10545-13:1998	GA
High acid and alkalins	ISO 10545-13:1998	GA
Resistance to staining	ISO 10545-14	Class 5
Resistance to cracking	ISO 10545-11:1997	Yes
Color stability, on exposure to light, UV rays	DIN 51094	Yes
Wet dynamic coefficient of friction	ANSI A326.3	≥0.60
Annex A: Ramp method footwear	UNE-EN-16165	R11
Annex B: Ramp method barefoot	UNE-EN-16165	Class C
Annex C: Pendulum method (PTV)	UNE-EN-16165	Class 3

Jeffrey Court does not warrant that any of its products will meet any testing parameter other than that measured at time of testing. Testing was completed by a certified lab and is representative only of product available for testing at the time. Jeffrey Court recommends that customers have tile independently tested to determine if the product meets or exceeds the requirements of the specifier or customer.

For additional details or questions please contact us at info@jeffreycourt.com.